



---

**Programme Area:** Smart Systems and Heat

**Project:** EnergyPath Operations

**Title:** EnergyPath Operations – Demonstration Presentation

---

**Abstract:**

A working prototype of EnergyPath Operations has been used to test the dynamic operation of elements of an architecture, as a set of detailed business processes across three domains: markets, physical assets, flows of information & control. This presentation was given to the ETI to provide an update at the end of the project on achievements and outputs from the work.

**Context:**

DNV GL and a partnership between Hitachi & EDF worked independently on a functional specification to develop the first phase of EnergyPath Operations - a software tool that allows designers to better understand the information and communications technology (ICT) solutions they will need to implement to deliver new home heating solutions.

A first version of this tool is now being developed by DNV GL and the Energy Systems Catapult. EnergyPath Operations will provide knowledge to users on how to design ICT systems, the cost implications of such designs and the viability of various systems.

This project complements the EnergyPath Networks software modelling tool which will be used in the planning of cost effective local energy systems.

# EPO demonstration

# CATAPULT

Energy Systems




Energy Systems Catapult  
June 2018

 EnergySysCat

 LinkedIn™

# ETI's Smart Systems and Heat Programme

Delivered by  
**CATAPULT**  
Energy Systems



“Creating future-proof and economic local heating solutions for the UK”

- Connecting together – the understanding of consumer needs and behaviour with the development and integration of technologies and new business models into...
- Delivering enhanced knowledge amongst industry and public sector
- Resulting in industry and investor confidence to implement from 2020 which enables a UK heat transition

## ETI members



**CATERPILLAR**



**Rolls-Royce**



Department for  
Business, Energy  
& Industrial Strategy

**EPSRC**  
Pioneering research  
and skills

**Innovate UK**  
Technology Strategy Board

## ETI programme associate


**HITACHI**  
Inspire the Next

The Energy Systems Catapult will deliver Phase One of the SSH programme as a supplier to the ETI following the transition of the SSH programme team to the Catapult. From 2017 the Catapult will be responsible for delivery of Phase Two of the programme independently of the ETI.

# Welcome


- Housekeeping
- **No Fire Alarms Expected Today**

# Agenda




Ref	Time	Agenda Item	Attended by	Lead	Duration
1	12:45	Arrive/welcome/coffee	All	-	15mins
2	13.00	Introductions and HSE	All	RL	5 mins
3	13.05	Demonstration - Outline of problem - Demonstration of EPO - Presentation of analysis - Outline of networks development	All	Project Team	95 mins
4	14.40	Q&A	All	Project Team	20 mins
6	15.00	Close	All	RL	10 mins

## Case Study




- Question: How do you go about installing 100 000 Hybrid Heat Pumps into a city the size roughly the size of Newcastle?
- Answer: Just fit them!
- Except: We all know reasons why you can't – what are they?
- Technology problems aren't high up the list!

# Architecture




# Conceptual Architecture – Iteratively Developed






# Risks



	De-risking approach		
	Paper based analysis	Whole systems model	Proto-type and trials
Whether distributed control can close out supply-demand sufficiently closely to manage system frequency, voltage, pressure, etc.		✓	?
Whether sufficient data quality can be obtained to price risk in experience based energy services			✓
Whether a shared service language can be formed to describe experience based energy services			✓
Whether the financial motivations of device vendors and service providers are sufficiently attractive to make it a commercially viable business	✓	✓	?
Whether consumers value the advanced services sufficiently to justify costs			✓
Whether weighting profiles can deliver sufficiently predictable aggregate response of distributed devices		✓	?
Whether energy service providers can build a sufficiently strong balance sheet to be a sufficiently low credit risk for long-term energy resource SLAs	✓		
Whether suitable contingency measures can be implemented, such as frequency responsive devices, to deal with major cyber-security threats		✓	?


# Thoughts on Architecture vs Design

- Architecture is the plan for the structure of something
- Design is the plan to create something
- Consider Building Architecture 'vs' Interior Design




- Working with stakeholders


# Logical Architecture



# Physical Design




# Example Operating Scenario – High Level Architecture




# Example Operating Scenario – Propose Analysis

- Evaluating (KPI):
  - Energy coming from Renewables (Wind)
  - Cost to the ESP of supplying energy (Electricity and Gas)
  - Delta between ESP physical supply and demand
  - Storage capacity required
- Based on:
  - Weather (Wind, Temperature) and Chaotic Occupant Behaviour
- Simulating:
  - Topology – HV Sub from Bridgend (7,484 domestic properties)
  - Variation in – Occupant Behaviour, HHP Allocation
  - Forecasting Metric – Smoothed Actual Demand
- Assuming:
  - Heat losses based on lumped convection and conduction
  - Energy Pricing – Ofgem values (assumed change for future)



# Demonstration

# Analysis : Simulation Test Cases




- Impact of Allocation of HHPs / Occupants to Domestic Properties
- Impact of weather over the heating season (Oct – Dec, Jan - Apr)

Case	Heating Appliance	Wind Turbines	Storage Charge / Discharge Rate
1	All Gas Heating 100% Combi-Gas Boilers	2	Infinite
2a	Penetration of HHP 70% Combi-Gas Boilers 30% HHP	4	10 MW Rate Limit
2b			

- 30% HHP – Double Electricity Consumption – Heating Same Contribution as Background
- Wind Turbines – Generation to Match Demand
- 10 MW Capacity – Charge Maximum Wind Generation



# Analysis : Approach




- Impact of Allocation of HHPs / Occupants to Domestic Properties (shown left)
- Same general trend, but have outliers – which depend on the variant topology:
  - combination of occupant profile and appliance – assigned to specific domestic properties
- Selected 'high', 'mid' and 'low' cases for a week, used these to run throughout season
- ... then look at impact of weather over heating season
  - which follows a general trend but has chaotic variations

# KPI – ESP Total Energy Cost

- Introducing HHP increases Energy Cost
- But Using Wind and Storage Helps to Reduce Cost



Average Seasonal Energy Cost per House



- Cost per House over Heating Season
- Reference Case Electricity bought from Spot Market
- Costs from Ofgem assumed price changes and assumed storage margin

# KPI - Imbalance



- Periods of significant imbalance (> 10% of demand) ... generally occur at volatile peaks in demand



- ... depends on local appliance control and consumer behaviour.

# KPI - Imbalance

- Forecasting (defined as low pass filter)
- ... improved prediction (lower time constant) ... reduces imbalance



- ... can look at different forecasting metrics and impact of prediction against technology cost


## Example Scenario

- **SOCIETAL OBJECTIVES:** Facilitates decarbonisation, by increasing renewable energy (wind generation) and decreasing gas usage.
- **COMMERCIALY ALIGNED:** Replacing Combi-Boilers with HHP more expensive. Using storage / wind has potential to reduce costs. Further economic analysis required.
- **SECURITY AND RESILIENCE:** Imbalance in supply and demand is pronounced during peak heating times when customer demand has significant volatilities.
- **PHYSICALLY CONSTRAINED:** Storage power and capacity greater than available at local level. Future scenarios may want to consider business models that manage inventory.
- **CONSUMER CENTRICITY:** Aggregated behaviour of customers and local appliance control have significant impact. Analysis motivates obtaining better understanding of this area.

Structure of analysis allows iterative development of scenario:


- .... Different Questions, Increase Scenario Scope, Enhancements to Modelling .....

# Electrical Networks Component




## Offline

### Allocation





### Allocation



### Dynamic simulation



# Electrical Network Topology



# Predictive Performance







## Future Challenges – Distribution Control


- At each voltage level, the distribution network will encounter technical issues – what are the potential control strategies to deal with them:

Control type	Description
Tap changer	mainly used for voltage control and keeping the system within limits
Energy storage system	Aggregators could use this for arbitrage but advantageous for the DNO in solving technical constraints – examples include voltage control and reverse power flow
Soft open points	Power flow between adjacent networks is automated based on network conditions
Demand side response	Turn up/ turn down of customer loads in periods of high and low network stress


# Future Challenges - Electrical Network Hierarchy



# Next Stages



# Conclusions



- Analysis is testing an implementation (a design) for an architecture, rather than the architecture itself.
  - Building support for a possible method or;
  - Triggering risk
- Program goals at April 2017:
  - to create and test a workflow for gradually defining 'slices' (successive layers of design detail) of a future Great Britain Energy System;
  - to explore options for a future Shared Ecosystem (markets which enable and encourage collective impact to create shared value); and
  - to build a first of a kind holistic simulator (EnergyPath® Operations) to enable interactions of a diverse range of Individual Actors within different options for the Shared Ecosystem to be understood.